



SITEL, spol. s r.o.

Company for Construction of Integrated Telecommunications

Domicile: Baarova 957/15, 140 00 Prague 4, Czech Republic

HQ: Nad Elektrárnou 1526/45, 106 00 Prague 10, Czech Republic

DECLARATION OF CONFORMITY

under the Act No. 90/2016 Sb., on Conformity Assessment of Products When Made Available in the Market, as amended

We:

SITEL, spol. s r.o.
Baarova 957/15
140 00 Prague 4
Company Registered No.: 44797320

declare under our sole responsibility that the following product meets the requirements of technical regulations, that the product is safe if used under conditions for use set by us and that we have adopted any and all measures that help us secure conformity of all products of the type stated below, which are introduced in the market, with both the technical documentation and requirements of the relevant governmental decree.

Product: Mesh trays

Type: DEFEM system (see Annex)

Manufacturer: SCHNEIDER ELECTRIC SVERIGE AB
Box 401, Mora, Sweden

Product Purpose: electrical assemblies, construction / installation of cable raceways

Conformity Assessment Method: No. 801393-01/01

The above mentioned product conforms to the following Standards: ČSN EN 61537:07 ed.čl. 7, 8, 9, 10.1, 10.9, 11.1, 14.2, ČSN EN ISO 2178:17

and Governmental Decree No. 118/2016 Sb. (2014/35/EU)

Additional Information: Certificate No. 1180559, dated 15th August 2018, valid until 31st August 2021 from the Electrotechnical Testing Institute (EZÚ) AO 201, Pod Lisem 129, 171 02 Prague 8 - Troja, Company ID No. 00001481

Place and Date of Issue: Prague, 27 August 2018

Miloš Schütter
Technical Director



Jan Novák
Statutory Director

tel: +420 267 198 111 fax: +420 267 198 222
e-mail: sitel@sitel.cz web: www.sitel.cz



bank. spojení: ČSOB Praha 5, č.ú.892803/0300
IČO 44797320 DIČ CZ44797320
spis.zn.: C 6725 u Městského soudu v Praze

Mesh trays	Material	Dimensions (mm)		Wire average diameter (mm)	
		A	B	C	D
Type					
53/45	Electrolytically galvanized	53	45	4	4
	Hot-dip galvanized EN1461	53	45	4	4
	Stainless steel	53	45	4	4
75 x 4/55	Electrolytically galvanized	75	55	4	4
	Hot-dip galvanized	75	55	4	4
	Stainless steel	75	55	4	4
75 x 5/55	Electrolytically galvanized	75	55	5	5
	Hot-dip galvanized	75	55	5	5
	Stainless steel	75	55	5	5
120/60	Electrolytically galvanized	120	60	5	5
	Hot-dip galvanized	120	60	5	5
	Stainless steel	120	60	5	5
220 /60	Electrolytically galvanized	220	60	5	5
	Hot-dip galvanized	220	60	5	5
	Stainless steel	220	60	5	5
320/60	Electrolytically galvanized	320	60	5	5
	Hot-dip galvanized	320	60	5	5
	Stainless steel	320	60	5	5
422/60	Electrolytically galvanized	422	60	5	6
	Hot-dip galvanized	422	60	5	6
	Stainless steel	422	60	5	6
522/60	Electrolytically galvanized	522	60	5	6
	Hot-dip galvanized	522	60	5	6
	Stainless steel	522	60	5	6
622/60	Electrolytically galvanized	622	60	5	6
	Hot-dip galvanized	622	60	5	6
	Stainless steel	622	60	5	6
120/110	Electrolytically galvanized	120	110	5	5
	Hot-dip galvanized	120	110	5	5
	Stainless steel	120	110	5	5
220/110	Electrolytically galvanized	220	110	5	5
	Hot-dip galvanized	220	110	5	5
	Stainless steel	220	110	5	5
320/110	Electrolytically galvanized	320	110	5	5
	Hot-dip galvanized	320	110	5	5
	Stainless steel	320	110	5	5
422/110	Electrolytically galvanized	422	110	5	6
	Hot-dip galvanized	422	110	5	6
	Stainless steel	422	110	5	6
522/110	Electrolytically galvanized	522	110	5	6
	Hot-dip galvanized	522	110	5	6
	Stainless steel	522	110	5	6
622/110	Electrolytically galvanized	622	110	5	6
	Hot-dip galvanized	622	110	5	6
	Stainless steel	622	110	5	6

Accessories: see manufacturer's catalogue

